



PRODUCT CODE	HEIGHT mm	VOLTAGE RATING	RIBS (Nos.)	CREEPAGE mm	Ø D mm	Ø d mm	A	INSERTS B	C
MV 5035	35	1.6 Kv	4	48	50	25	-	M-08 X 15 Lg	M-08 X 15 Lg
MV 7535	35	1.6 Kv	4	67	75	30	-	M-10 X 15 Lg	M-10 X 15 Lg
MV 6040	40	3.5 Kv	1	55	60	36	M-10 X 15 Lg	M-08 X 12 Lg	M-10 X 15 Lg
MV 4050	50	3.5 Kv	1	55	40	-	M-10 X 15 Lg	-	M-10 X 15 Lg
MV 5050	50	3.5 Kv	4	65	50	25	-	M-08 X 20 Lg	M-08 X 20 Lg
MV 7550	50	3.5 Kv	4	82	75	30	-	M-10 X 20 Lg	M-10 X 20 Lg
MV 606560	60	5.5 Kv	2	90	60/65	36	M-12 X 20 Lg	M-08 X 20 Lg	M-12 X 20 Lg
MV 859060	60	5.5 Kv	2	90	85/90	40	M-16 X 20 Lg	M-10 X 20 Lg	M-16 X 20 Lg
MV 6075	75	6.8 Kv	2	112	60	36	M-10 X 20 Lg	M-06 X 15 Lg	M-12 X 25 Lg
PDMV 6075	75	6.8 Kv	2	112	60	36	M-10 X 20 Lg	M-08 X 15 Lg	M-12 X 25 Lg
MV 9580	80	6.8 Kv	1	92	90	55	-	M-10 X 20 Lg	M-16 X 30 Lg
MV 6090	90	8.5 Kv	3	140	60	36	M-10 X 20 Lg	M-06 X 15 Lg	M-12 X 25 Lg
PDMV 6090	90	8.5 Kv	3	140	60	36	M-10 X 20 Lg	M-08 X 15 Lg	M-12 X 25 Lg
MV 9011082	110	12 Kv	4	209	82/90	40	-	M-10 X 15 Lg	M-12 X 20 Lg
MV 60130	130	12 Kv	5	200	60	36	M-12 X 25 Lg	M-06 X 15 Lg	M-16 X 35 Lg
PDMV 60130	130	12 Kv	5	200	60	36	M-12 X 25 Lg	M-08 X 15 Lg	M-16 X 35 Lg
MV 75130	130	12 Kv	5	215	75	45	M-16 X 35 Lg	M-10 X 20 Lg	M-20 X 35 Lg
MV 75130/2*	130	12 Kv	5	215	75	45	M-12 X 25 Lg	M-08 X 20 Lg	A-B
MV 75130/7	130	12 Kv	7	256	75	45	M-16 X 35 Lg	M-10 X 20 Lg	M-20 X 40 Lg
MV 90130	130	12 Kv	7	372	90	36	-	M-16 X 30 Lg	M-20 X 35 Lg
MV 8614580	145	16 Kv	7	260	80/86	40	-	M-10 X 15 Lg	M-12 X 20 Lg
MV 90150	150	16 Kv	7	392	90	36	-	M-16 X 30 Lg	M-20 X 35 Lg
MV 70210	210	22 Kv	9	285	70	36	M-10 X 25 Lg	M-06 X 15 Lg	M-16 X 55 Lg
PDMV 70210	210	22 Kv	9	285	70	36	M-10 X 25 Lg	M-08 X 15 Lg	M-16 X 55 Lg
MV 70210/2	210	22 Kv	9	285	70	36	M-12 X 25 Lg	M-08 X 20 Lg	A-B
MV 80300	300	35 Kv	12	450	80	36	M-10 X 25 Lg	M-06 X 15 Lg	M-16 X 75 Lg
PDMV 80300	300	35 Kv	12	450	80	36	M-10 X 25 Lg	M-08 X 15 Lg	M-16 X 75 Lg
MV 95300	300	35 Kv	12	630	95	46	M-16 X 55 Lg	M-10 X 20 Lg	M-22 X 65 Lg

• Material : Cast Resin / DMC (Dough Moulding Compound) UL File No. QEUY2.E249670 (Halogen Free)

++ same insert configuration on both sides

• All Dimensions are in MM

• Insert : Brass / Mild Steel (Zinc Passivated)

• Insert Material detail on page no. 66

• All Insulators are certified

• For technical details of Busbar support & Insulator, please refer POWERMAT TECHNICAL NOTES - 01/15.

• For checking the suitability of a support & insulator for a fault current, please ask for POWERMAT FAULT LEVEL CALCULATOR Software.